

- Narrow chassis, low stowed height, can be transported easily through doorways and in passenger elevators.
- Small inside turning radius allows for flexible use in narrow spaces, improving work efficiency.
- Three-stage integrated rotatable telescopic oil cylinder, reliable and durable.
- Intelligent self-diagnostic system for quick troubleshooting.
- Configure an extension deck to increase the working range.


LGMG VERTICAL MAST LIFTS


SPECIFICATIONS

MODELS	M123	30TE
Measurements	Imperial	Metric
Working Height Max.	18'8"	5.7m
Platform Height (Raised)	12'2"	3.7m
Platform Size	4'4"x2'6"	1.33x0.75m
Overall Length	4'7''	1.39m
Overall Width	2'6''	0.76m
• Overall Height (Stowed)	5'6''	1.69m
• Wheelbase	3'5''	1.04m
Extension Deck	1'4"	0.4m
Ground Clearance (Stowed/Raised)	3"/1"	68/15mm
PRODUCTIVITY		
Max. Platform Occupants	1(in) / 0(out)	
Platform Capacity	507 lbs	230kg
Platform Capacity- Extension Deck	249 lbs	113kg
Drive Mode	Front wheels drive	
Drive Speed (Stowed)	2.5mph	4km/h
Drive Speed (Raised)	0.31mph	0.5km/h
Gradeability	25%	
Tire Size	13"x4"	323x100mm
POWER		
Power Source	24V (2x12V),145Ah,AGM	
HYDRAULIC SYSTEM		
Hydraulic Oil Capacity	1.5 gal	5.5L
WEIGHT		
	1,852 lbs	840kg

STANDARD FEATURES		
Proportional control	Emergency stop device	
Horn/Hour meter	Manual brake release	
Double swing gate	Charging protection system	
Emergency descent	Descent alarm with flashing beacon	
Pothole guard	Front wheel brake	
Full-height drive	Front wheel steering, front wheel drive	
Tilt alarm	Telematics connector	
Platform tool box	Solid non-marking tires	
Transport Forklift Holes		

OPTIONAL	
AC power to platform	Biodegradable hydraulic oil
Telematics	





Please contact LGMG or a local dealer for more details.

LGMG reserves the right to change technical data without prior notice. All photos and pictures in this brochure are for promotional purposes only.



